


MUSCAT/Muscat Intl
OMAN
RNP RWY 26R



Amendment: Frequency Table Updated

Holding Instruction/Areas RNP RWY 26R

Path descriptor	Fix identifier	Inbound course M (T)	Leg Distance	Turn direction	Minimum altitude	Maximum altitude	Speed	Magnetic variation	Navigation performance
Hold	MCT VOR	091° (092.0°)	1 MIN	L	6000		210 KT	1.4°E	

Route Description: RNP RWY 26R

Path descriptor	Fix identifier	Flyover	Course Magnetic (True)	Turn direction	Altitude	Speed limit	Magnetic variation	Distance	Navigation performance
IF	M15ER				+4500	220 KT	1.4°E		RNP APCH
TF	MURMA		264° (265.1°)		+3400		1.4°E	3.2	RNP APCH
TF	M07ER		264° (265.1°)		+2200		1.4°E	5.4	RNP APCH
TF	<u>RW26R</u>	Y	264° (265.1°)		+69		1.4°E	6.5	RNP APCH

MISSED APPROACH

CF	<u>MS750</u>	Y	264° (265.0°)			220 KT	1.4°E		RNP APCH
TF	MS755		290° (291.0°)	R		220 KT	1.4°E	13.0	RNP APCH
TF	MS760		020° (020.9°)	R		220 KT	1.4°E	6.6	RNP APCH
TF	MS765		085° (085.9°)	R		220 KT	1.4°E	8.1	RNP APCH
TF	MCT VOR		162° (163.7°)	R	+6000	220 KT	1.4°E	12.6	RNP APCH
HM	MCT VOR		091° (092.0°)	L	+6000	210 KT	1.4°E	1 min	RNP APCH

Aeronautical Data Tabulation: RNP RWY 26R

Waypoint / Fix	Latitude	Longitude	Latitude (MIN)	Longitude (MIN)	Notes
M15ER	N23°37'50.73"	E058°34'14.98"	N23°37.846'	E058°34.250'	
MURMA (IF)	N23°37'34.20"	E058°30'44.72"	N23°37.570'	E058°30.745'	
M07ER (FAF)	N23°37'06.15"	E058°24'49.95"	N23°37.103'	E058°24.833'	
RW26R (MAPT)	N23°36'32.11"	E058°17'43.65"	N23°36.535'	E058°17.728'	
MS750	N23°36'11.91"	E058°13'32.53"	N23°36.199'	E058°13.542'	
MS755	N23°40'50.95"	E058°00'20.96"	N23°40.849'	E058°00.349'	
MS760	N23°47'02.00"	E058°02'55.00"	N23°47.033'	E058°02.917'	
MS765	N23°47'36.75"	E058°11'45.47"	N23°47.613'	E058°11.758'	
MCT VOR	N23°35'28.04"	E058°15'36.48"	N23°35.474'	E058°15.607'	

Non precision final approach 3.07° (5.36%).